

Product Data Sheet

			Order No.	Size	Sterility	Packaging	Packaging Unit
pluriStrainer 5µm	0	\bigcirc	43-50005-00	1 pc.	Non-sterile	Loose	/ Pack
		\bigcirc	43-50005-01	1 pc.	Sterile	Single-packed	/ Pack
			43-50005-03	25 pcs.	Sterile	Single-packed	25 pcs. / Pack*
		Ō	43-50005-13	25 pcs.	Sterile	Single-packed	25 pcs. / Pack
		Õ	43-50005-50	50 pcs.	Non-sterile	Loose	50 pcs. / Pack

* includes same amount of sterile Connector Rings

Specification

Mesh Size:	5 µm		
Strainer Color:	yellow		
LOT:	stated on the label		
Mesh Material:	PET		
Housing Material:	PE		

Applications

- Obtaining a real single cell suspension after enzymatic digestion of mammary tissue and organoids
- Dissociation of cells from other primary tissue
- Preparation of a single cell suspension of blood cells from bone marrow, pancreas, thymus, lymph nodes and others
- Preparation of real single cell suspension for flow cytometry
- Faster and easier alternative to gauze filtration
- Filtering agglutinative proteins produced in inactivation serum
- Sieving of complex and viscous liquids (in combination with Connector Ring & Syringe for low pressure)

Component Description

The pluriSelect cell strainer - pluriStrainer is a sterile sieving device to obtain real single cell suspensions or to remove cell aggregates. Its unique design features improved ventilation to avoid clogging - furthermore it can be combined with a Connector Ring (41-50000-03) to use low pressure which supports the filtration. pluriStrainer® are stackable to allow direct filtration with different mesh sizes. pluriStrainer® can be inverted to recover the sieved material. For large sample volumes it can be combined with a funnel. It fits into any 50 mL centrifuge (conical) tube and is available in mesh sizes from 1 - 500 μ m.

Usage



Simple Sieving

Attach pluriStrainer[®] to a sterile 50 mL centrifuge tube. Then, add sample material onto the strainer and filter sample.



<u>Reversed</u>

To obtain the larger fraction, take off the pluriStrainer®, turn it upside down onto another 50 ml tube and flush back the sample from the pluriStrainer®.



Stacked

time

Stacking of pluriStrainer® with different mesh sizes allows for straining various cell sizes at the same



With Funnel You can add up to 24 mL sample material on top.

With Connector Ring pluriStrainer® in combination with a Connector Ring allows to control the rate of flow by opening or closing the Luer-Lock.

With Connector Ring + Syringe If you add a syringe to the Connector Ring, it is possible to force low pressure to support the straining of rough sample material while pulling the piston.

Component Storage Condition

The product is stable until the expiry date stated on the label when stored unopened as indicated below. Avoid bacterial contamination.

Product Type	Storage Condition	Stability	Important Notes	
pluriStrainer	room temperature	stated on the label	-	

Warning and Limitations

The product is for research and development only, not for diagnostic or therapeutic use.

pluriSelect - USA 8912 Bancroft View Drive, San Diego (Spring Valley), CA 91977, US Phone: +1 619-202-4297 | Fax: +1 619-828-8003 sales-support@pluriselect-usa.com www.pluriselect.com

Advanced Usage